Listing of Claims

1. (currently amended) A combination adjuvant, comprising:

wherein said adjuvant is dry and free flowing.

a plurality of water-soluble nitrogen-based fertilizer granules; and
a drift reducing agent;
wherein said drift reducing agent is impregnated within the outer portion of said granules,
wherein said adjuvant does not contain a powdered drift reducing agent, and

- (original) The combination adjuvant as claimed in claim 1, wherein said fertilizer granules are ammonium sulfate granules.
- 3. (original) The combination adjuvant as claimed in claim 2, wherein said drift reducing agent is selected from the group consisting of anionic polyacrylamide; non-ionic polyacrylamides; cationic polyacrylamides; polymers of acrylic acid; copolymers of acrylic acid; methacrylic acids and their salts; methylacrylamides and their copolymers, derivatives and mixtures thereof; polyacrylonitrile, its hydrolysis products, and copolymers, derivatives and mixtures thereof; polymers of ethylene oxides; and polymers of alkylene oxides.
- 4. (original) The combination adjuvant as claimed in claim 3, wherein said drift reducing agent is polyacrylamide.
- (original) The combination adjuvant as claimed in claim 4, wherein said drift reducing agent is anionic polyacrylamide.

6. (currently amended) The combination adjuvant as claimed in claim 3, further comprising a drying agent selected from the group consisting of sodium sulfate, calcium bentonite, diatamaceouos silica, polyethylene glycol flakes, polyethylene glycol, (flakes, prill or powder), polyethylene glycol flakes, polyethylene glycol prill, polyethylene glycol powder, calcium silicate, magnesium silicate, aluminum silicate, sodium silicate, polyvinylpyrrolidone, polysaccharide, free flowing silica, mica, cellulose powder, kraft lignin, lignosulfonates, sulfosuccinates, sodium salt of polymerized naphthalene sulfonic acid, sodium salt of carboxylated polyelectrolyte, POE stearates, dioleates, sodium butyl naphthalene sulfonates, sodium sulfonate of naphthalene formaldehyde condensate, di-nbutyl sodium naphthalene sulfonate, di-isopropyl sodium naphthalene sulfonate, sodium dodecylbenzene sulfonate, polyacrylates, polycarboxylates, solid block co-polymers, POE lauryl alcohol and sorbitan stearates.

- (original) The combination adjuvant as claimed in claim 6, wherein said drying agent is sodium sulfate.
- 8. (currently amended) The combination adjuvant as claimed in claim 3, further comprising an anti-caking agent selected from the group consisting of silicon dioxide, tricalcium phosphate, , silicas, (fumed or free flowing), fumed silicas, free flowing silicas, hydrophobic starch derivatives, powdered cellulose, calcium silicate, magnesium silicate, aluminum silicate, sodium silicate, polyacrylic acid and sodium salts thereof, and sodium polyalkyl naphthalene sulfonate.
- 9. (original) The combination adjuvant as claimed in claim 8, wherein said anti-caking agent is silicon dioxide.

Serial No.: 10/035,486

Docket No.: 505907-0002

10. (currently amended) The combination adjuvant as claimed in claim 6, further comprising an anti-caking agent, selected from the group consisting of silicon dioxide, tricalcium phosphate, , silicas, (fumed or free flowing), fumed silicas, free flowing silicas, hydrophobic starch derivatives, powdered cellulose, calcium silicate, magnesium silicate, aluminum silicate, sodium silicate, polyacrylic acid and sodium salts thereof, and sodium polyalkyl naphthalene sulfonate.

- 11. (currently amended) A combination adjuvant, comprising:
 - a plurality of ammonium sulfate granules;
 - a polyacrylamide drift reducing agent, wherein said polyacrylamide drift reducing agent is impregnated within the outer portion of said ammonium sulfate granules;

sodium sulfate; and

silicon dioxide,

wherein said adjuvant does not contain a powdered drift reducing agent.

12. (currently amended) A method for making a combination adjuvant, comprising the steps of: providing a liquid drift reducing agent;

providing dry ammonium sulfate granules; and

mixing said liquid drift reducing agent with said ammonium sulfate granules until thoroughly mixed to form an ammonium sulfate/drift reducing agent mixture, and wherein said method excludes the step of adding a powdered drift-reducing agent.

- 13. (original) The method as claimed in claim 12, wherein said liquid drift reducing agent comprises between 0.01 and 25.0 weight percent of the ammonium sulfate/drift reducing agent mixture.
- 14. (original) The product produced according to the method of claim 12.

15. (currently amended) The method as claimed in claim 12, further comprising the steps of:
adding to said ammonium sulfate/drift reducing mixture a drying agent selected from the
group consisting of sodium sulfate, calcium bentonite, diatamaceouos silica, ,
polyethylene glycol, (flakes, prill or powder), polyethylene glycol flakes, polyethylene
glycol prill, polyethylene glycol powder, calcium silicate, magnesium silicate, aluminum
silicate, sodium silicate, polyvinylpyrrolidone, polysaccharide, free flowing silica, mica,
cellulose powder, kraft lignin, lignosulfonates, sulfosuccinates, sodium salt of
polymerized naphthalene sulfonic acid, sodium salt of carboxylated polyelectrolyte, POE
stearates, dioleates, sodium butyl naphthalene sulfonates, sodium sulfonate of
naphthalene formaldehyde condensate, di-n-butyl sodium naphthalene sulfonate, diisopropyl sodium naphthalene sulfonate, sodium dodecylbenzene sulfonate,
polyacrylates, polycarboxylates, solid block co-polymers, POE lauryl alcohol and
sorbitan stearates; and

mixing said drying agent with said ammonium sulfate/drift reducing agent mixture.

16. (currently amended) The method as claimed in claim 15, further comprising the steps of:

adding to said ammonium sulfate/drift reducing agent mixture an anti-caking agent
selected from the group consisting of silicon dioxide, tricalcium phosphate, silicas,
(fumed or free flowing), fumed silicas, free flowing silicas, hydrophobic starch
derivatives, powdered cellulose, calcium silicate, magnesium silicate, aluminum silicate,
sodium silicate, polyacrylic acid and sodium salts thereof, and sodium polyalkyl
naphthalene sulfonate; and
mixing said anti-caking agent with said ammonium sulfate/drift reducing agent mixture

and said drying agent to form an adjuvant mixture.

17. (original) The product produced according to the method of claim 16.

18. (original) The method as claimed in claim 16, wherein said liquid drift reducing agent is liquid polyacrylamide.

- 19. (original) The method as claimed in claim 18, wherein said drying agent comprises between 0.01 and 20.0 weight percent of said adjuvant mixture and said anti-caking agent comprises between 0.01 and 20.0 weight percent of said adjuvant mixture.
- 20. (original) The product produced according to the method of claim 19.